Model identifier(s): Scar				Ne					
Indirect heating functionality				No					
Direct heat output(kW)				7.2					
Indirect heat output(kW	()			N.A					
						Emissions from space heating at nominal heat output			
			Preferred fuel	d Model		OGC	СО	NO _x	
Fuel				(Only one)	identifier(s)	[X] mg/Nr	n ₃ (13 %	6 O ₂)	
Wood logs with moisture content \leq 25%				Yes	No	22	42	893	95
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when op	erating with	the prefer	red fuel						
Seasonal space heating er		•		69					
Energy Efficiency Class	- 07	, ist 1		Α					
Energy Efficiency Index (E	EI)			105					
Item	Symbol	Value	Unit	Item		Symbol	l Value		Unit
Heat output	Symbol	vatue	Onte	Use efficiency (NCV as re					Onte
Nominal heat output	P_{nom}	7.2	kW	Useful efficiency at nominal heat output		η _{th, nom}	_{om} 79		%
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful efficiency at minimum heat output (indicative)		η _{th, min}	N.A.		%
Auxiliary electricity cons	umption			1 (,	m temper	atura c	ontrol /	alaakaaa
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	m temperature contro no room [yes/no]			serect one	
At minimum heat output	el _{min}	x,xxx	kW	two or more	s, no l	s, no [yes/		Yes	
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room	om [yes/no]			
				with electronic room temp control		oerature	re [yes/no]		
				with electronic room temperatur control plus day timer			[yes/no]		
				with electronic room temperatu control plus week timer		oerature	[yes/no]		
				Other control options (multiple			ctions	oossible)	
				room temp presence d	room temperature control, v presence detection		[ye	s/no]	
				room temp open windo	l, with	[yes/no]			
				with distan	ce control opti	on	[ye	s/no]	
Permanent pilot flame p	ower requir	ement							
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW				1		
Contact details	Name and a	address of t	he supplier:		Brian Ørum, R&E) Manager, Sca	n A/S, Der	nmark	