Model identifier(s): Scar	1004 VE								
Indirect heating functionality				No					
Direct heat output(kW)				8					
Indirect heat output(kW)				N.A					
					Emissions from space heating at nominal heat output				
				Preferred fuel	Model	PM	OGC	СО	NO <sub>x</sub>
Fuel			(Only one)	identifier(s)	[X] mg/Ni	m <sub>3</sub> (13 %	02)		
Wood logs with moisture content ← 25%				Yes	No	22	42	893	95
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when operating with the preferred fuel									
Seasonal space heating er	nergy efficie	ncy η <sub>s</sub> [%]		69					
Energy Efficiency Class				А					
Energy Efficiency Index (EEI)				105					
ltem	Symbol	Value	Unit	lt lt	Symbo	Symbol Value		Unit	
Heat output				Use efficiency (NCV as re		ceived)			
Nominal heat output	P <sub>nom</sub>	8	kW	Useful efficiency at nominal heat output		$\eta_{\text{th, nom}}$	$\eta_{th, nom}$ 79		%
Minimum heat output (indicative)	P <sub>min</sub>	N.A.	kW	Useful effic minimum he output (ind	$\eta_{\text{th, min}}$	N.A.		%	
Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
At nominal heat output	el <sub>max</sub>	x,xxx	kW	single stage temperatur	no room [yes/n				
At minimum heat output	el <sub>min</sub>	x,xxx	kW	two or more	s, no [yes/		s/no]	Yes	
In standby mode	el <sub>sB</sub>	x,xxx	kW	with mecha temperatur	t room [yes		s/no]		
				with electro	perature	[yes/no]			
				with electro control plus	perature	[yes/no]			
				with electro control plus	perature	[yes/no]			
				Other cont	nultiple sele	ections p	ossible)		
				room temp presence d	l, with	[yes	s/no]		
				room tempo open windo	l, with	vith [yes/no]			
			with distance control option			[yes	s/no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW			) //	1		
Contact details	ivame and a	address of th	ie supplier:		Brian Ørum, R&I	D Manager, Sca	n A/S, Denr	nark	