Model identifier(s): Scar	n 80									
Indirect heating functionality				No						
Direct heat output(kW)				6						
Indirect heat output(kW)				N.A						
					Emissions from space heating at nominal heat output					
		Preferred fuel	Model		OGC	CO	NO _x			
Fuel				(Only one)	identifier(s)	[X] mg/Nr	- J -			
Wood logs with moisture content ← 25%				Yes	No	12	61	833	84	
Compressed wood with moisture content < 12%				No	No					
Other woody biomass				No	No					
Anthracite and dry steam coal				No	No					
Hard coke				No	No					
Low temperature coke				No	No					
Bituminous coal				No	No					
Lignite briquettes				No	No					
Peat briquettes				No	No					
Blended fossil fuel briquettes				No	No					
Other fossil fuel				No	No					
Blended biomass and fossil fuel briquettes				No	No					
Other blend of biomass and solid fuel				No	No					
Characteristics when op	erating with	the prefer	red fuel							
Seasonal space heating er	<u> </u>	•		74						
Energy Efficiency Class		/ .I _S []		A+						
Energy Efficiency Index (E	:FI)			112						
ltem		Value Unit Item			<u> </u>	Cumbal	\/_I		Unit	
	Symbol	value	Unit	Use efficiency (NCV as re		Symbol			Unit	
Heat output				Use efficiency (NCV as re						
Nominal heat output	P _{nom}	6	kW	nominal hea	inal heat output		η _{th, nom} 84		%	
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful effic minimum he output (indi	$\eta_{\scriptscriptstyle th, min}$ N.A.		A.	%		
Auxiliary electricity consumption Type of heat output/room temperature control (select one)	
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	no room [yes/n					
At minimum heat output	el _{min}	x,xxx	kW	two or more	s, no l	no [yes/no]		Yes		
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room [yes		/no]			
				with electro	perature	erature [yes/no]				
				with electro control plus	perature	ature [yes/no]				
				with electro control plus	perature	[yes/no]				
				Other control options (multipl			ections po	ossible)		
				room tempo presence do	l, with	[yes,	/no]			
				room tempo open windo	, with [yes/no]		/no]			
				with distan	ce control opti	on	[yes,	/no]		
Permanent pilot flame p										
Pilot flame power requirement (if applicable)	P_{pilot}	N.A.	kW				1			
Contact details	Name and address of the supplier: Dintact details Brian Ørum, R&D Manager, Scan A/S, Denmark									